



Ventable, bypass/restrictive, fixed-orifice, priority flow controls take an input flow at port 1 and use it to satisfy the priority flow at port 3. If the input flow exceeds the priority flow requirement, the excess is bypassed out port 2. The bypass flow may be used in a secondary circuit. A vent port (port 4) allows these valves to be controlled remotely.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Nominal Vent Flow	0,75 L/min.
Maximum Input Flow	240 L/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990023007
Seal kit - Cartridge	Polyurethane: 990023002
Seal kit - Cartridge	Viton: 990023006

CONFIGURATION OPTIONS

Model Code Example: FVEAXAN

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A Replaceable Orifice .2 - 25 gpm (0,8 - 95 L/min.)	N Buna-N	N Standard Material/Coating
K Handknob		V Viton	/LH Mild Steel, Zinc-Nickel
L Tuning Adjustment			