



Free-flow, side-to-nose cheater check valves function as a standard 2-port check valve in a 3-port cavity with port 3 of the cartridge blocked off. These valves are useful in circuits where a check valve is required in an existing three port cavity.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                         |
|---|-------------------------|
| Maximum Operating Pressure                | 350 bar                 |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,07 cc/min.            |
| Seal kit - Cartridge                      | Buna: 990011007         |
| Seal kit - Cartridge                      | Polyurethane: 990011002 |
| Seal kit - Cartridge                      | Viton: 990011006        |

**CONFIGURATION OPTIONS**

**Model Code Example: CXCEXCN**

| <b>CONTROL</b>          | <b>(X) CRACKING PRESSURE</b>  | <b>(C) SEAL MATERIAL</b>   | <b>(N) MATERIAL/COATING</b>                                     |
|-------------------------|---|----------------------------|---|
| <b>X</b> Not Adjustable | <b>C</b> 30 psi (2 bar)<br>A 4 psi (0,3 bar)<br>B 15 psi (1 bar)<br>D 50 psi (3,5 bar)<br>E 75 psi (5 bar)<br>F 100 psi (7 bar) | <b>N</b> Buna-N<br>V Viton | <b>Standard Material/Coating</b><br>/LH Mild Steel, Zinc-Nickel |