



Free-flow, nose-to-side check valves with a bypass orifice allow free flow from port 1 to port 2. A customer specified orifice is included to restrict flow from port 2 to port 1. See technical data below for orifice range.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 2,7 mm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

CONFIGURATION OPTIONS

Model Code Example: CNDCXCN

CONTROL	(X) SETTING RANGE	(C)	SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C 30 psi (2 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)		N Buna-N	Standard Material/Coating
L Manual Load Release	A 4 psi (0,3 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)		V Viton	IAP Stainless Steel, Passivated
	B 15 psi (1 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)			ILH Mild Steel, Zinc-Nickel
	D 50 psi (3,5 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)			
	E 75 psi (5 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)			
	F 100 psi (7 bar) Cracking Pressure, .016 - .107 in. (0,4 - 2,7 mm)			