



High accuracy, synchronizing flow divider/combiners are sliding-spool, pressure-compensated devices used to split flow in one direction and combine flow in the opposite direction. With a synchronizing feature, these valves can be used to allow two hydraulic cylinders to fully stroke and synchronize at the end of the stroke. When the first cylinder has reached the end of its stroke, a pressure-compensated, reduced flow is metered to or from the second cylinder until it also reaches the end of its stroke.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Minimum Input Flow	50% ±2.5%
Divisional Accuracy at Max Input Flow	50% ±1.5%
Pressure Drop at Minimum Rated Input Flow	2 bar
Pressure Drop at Maximum Rated Input Flow	24 bar
Seal kit - Cartridge	Buna: 990033007
Seal kit - Cartridge	Polyurethane: 990033002
Seal kit - Cartridge	Viton: 990033006

**CONFIGURATION OPTIONS**

**Model Code Example: FSERXAN**

<b>CONTROL</b>	<b>(X) FLOW SPLIT</b>	<b>(A) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
X Not Adjustable	A 50/50	N Buna-N V Viton	Standard Material/Coating /LH Mild Steel, Zinc-Nickel