



This solenoid-operated 2-way, 2-position cartridge is a direct-acting, balanced spool directional valve. The valve is available in either a normally open or normally closed configuration.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Response Time - Typical	50 ms
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Switching Frequency	15000 cycles/hr
Manual Override Force Requirement	33 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Seal kit - Cartridge	Buna: 990413007
Seal kit - Cartridge	EPDM: 990413014
Seal kit - Cartridge	Viton: 990413006

- NOTES**
- Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.
  - An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

**CONFIGURATION OPTIONS**

Model Code Example: **DLDAXCN**

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) COIL *
<b>X</b> No Manual Override	<b>C</b> Normally Closed	<b>N</b> Buna-N	No coil
<b>M</b> Manual Override	<b>H</b> Normally Open	<b>E</b> EPDM	<b>212</b> DIN 43650-Form A, 12 VDC
<b>D</b> Twist/Lock (Dual) Manual Override		<b>V</b> Viton	<b>224</b> DIN 43650-Form A, 24 VDC
<b>L</b> Twist/Lock (Detent) Manual Override			<b>712</b> Twin Lead, 12 VDC
<b>T</b> Twist (Momentary) Manual Override			<b>724</b> Twin Lead, 24 VDC
			<b>912</b> Deutsch DT04-2P, 12 VDC
			<b>924</b> Deutsch DT04-2P, 24 VDC

\* Additional coil options are available

**MATERIAL/COATING**

Standard Material/Coating