



Needle valves with reverse-flow check are fully adjustable orifices used to regulate flow. They are infinitely adjustable from fully closed up to the maximum orifice diameter. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1. They are not pressure compensated.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.
Adjustment - No. of CCW Turns from Fully Closed to Fully Open (Web) Sort	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990018007
Seal kit - Cartridge	EPDM: 990018014
Seal kit - Cartridge	Polyurethane: 990018002
Seal kit - Cartridge	Viton: 990018006

CONFIGURATION OPTIONS

Model Code Example: NCGBLCN

CONTROL	(L) REVERSE FLOW CHECK	(C) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	C 30 psi (2 bar)	N Buna-N	Standard Material/Coating
H Calibrated Handknob with Detent Lock	A 4 psi (0,3 bar)	E EPDM	/AP Stainless Steel, Passivated
K Handknob	E 75 psi (5 bar)	V Viton	/LH Mild Steel, Zinc-Nickel
Y Tri-Grip Handknob			