



Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. A variety of flow rates are available.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	EPDM: 990008014
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006

CONFIGURATION OPTIONS

Model Code Example: FXAAXAN

CONTROL	(X) FLOW RATE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A 15 in ³ /min. (250 cc/min.) B 20 in ³ /min. (330 cc/min.) D 40 in ³ /min. (660 cc/min.) F 60 in ³ /min. (1 L/min.) H 80 in ³ /min. (1.3 L/min.) J 100 in ³ /min. (1.6 L/min.) L 120 in ³ /min. (2.0 L/min.)	N Buna-N E EPDM V Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel