



Kick-down sequence valves will kick completely open and remain open once the pressure at the inlet (port 1) exceeds the valve setting, creating an unrestricted flow path from port 1 to port 2 (sequence). The pressure setting at port 1 is relative to the drain (port 3). The valve remains open as long as the pressure at port 1 exceeds the pressure at port 2. To reset the valve, pressure at port 1 must fall below the setting of the valve, flow from port 1 to port 2 must cease, and pressure at port 2 must be equal to or greater than the pressure at port 1.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Factory Pressure Settings Established at	Kick down point
Maximum Operating Pressure	350 bar
Response Time - Typical	25 ms
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990019007
Seal kit - Cartridge	Polyurethane: 990019002
Seal kit - Cartridge	Viton: 990019006

**CONFIGURATION OPTIONS**
**Model Code Example: SQJBLAN**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L Standard Screw Adjustment		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N	
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting		V Viton	
K Handknob		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting			
		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting			
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting			