



This valve is a pilot to open check valve with a bypass orifice. It incorporates a sealed pilot, a steel seat, and is non-vented. It allows free flow from the valve (port 2) to the load (port 1) and restricts flow in the opposite direction. Pressure at the pilot (port 3) will open the valve from port 1 to port 2. The pilot pressure needed at port 3 to open the valve is directly proportional to the load pressure at port 1. Pressure at port 2 directly opposes the pilot pressure. Note: The bypass orifice diameter is specified by the customer. See Technical Data below for the allowable orifice range.

TECHNICAL DATA

Pilot Ratio	3:1
Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 3,4 mm
Seal kit - Cartridge	Buna: 990202007
Seal kit - Cartridge	Polyurethane: 990002002
Seal kit - Cartridge	Viton: 990202006

CONFIGURATION OPTIONS

Model Code Example: CNEEXCN

CONTROL	(X) SETTING RANGE	(C) SEAL MATERIAL	(N)
X Not Adjustable	<p>C 30 psi (2 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p> <p>A 4 psi (0,3 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p> <p>B 15 psi (1 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p> <p>D 50 psi (3,5 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p> <p>E 75 psi (5 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p> <p>F 100 psi (7 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)</p>	<p>N Buna-N</p> <p>V Viton</p>	