



This valve is a fixed-orifice, non-pressure-compensated flow control with a reverse flow check. The flow setting is specified by the user and is set at the factory.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 3,4 mm
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	Viton: 990203006

**CONFIGURATION OPTIONS**

**Model Code Example: CNECXCN**

CONTROL	(X) SETTING RANGE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>C</b> 30 psi (2 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm) <b>A</b> 4 psi (0,3 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm) <b>B</b> 15 psi (1 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm) <b>D</b> 50 psi (3,5 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm) <b>E</b> 75 psi (5 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm) <b>F</b> 100 psi (7 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating /AP Stainless Steel, Passivated