



Vented, balanced load control valves combine a balanced modulating element with a reverse flow check. The check valve allows free flow from the directional valve (port 2) to the load (port 1) while the pilot to open modulating element controls flow from port 1 to port 2. Pilot pressure at port 3 determines the flow setting. Backpressure at port 2 does not affect the flow setting because the spring chamber references the vent (port 4).

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at Reseat	See Technical Features
Check Cracking Pressure	1,7 bar
Seal kit - Cartridge	Buna: 990024007
Seal kit - Cartridge	Polyurethane: 990024002
Seal kit - Cartridge	Viton: 990024006

**CONFIGURATION OPTIONS**

**Model Code Example: MWIMXIN**

CONTROL	(X)	MINIMUM CONTROL PRESSURE	(I)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>I</b> 300 psi (20 bar)		<b>N</b> Buna-N		Standard Material/Coating
		E 75 psi (5 bar)		V Viton		JAP Stainless Steel, Passivated
		G 150 psi (10,5 bar)				
		H 200 psi (14 bar)				
		K 450 psi (33 bar)				
		M 525 psi (36,7 bar)				