



Flow dividers are sliding-spool, pressure-compensated devices used to split oil flow to two different branches of a circuit in a designated ratio. These valves are suitable for applications that use the following: unidirectional hydraulic motors, hydraulic cylinders where flow division in one direction only is required, and multiple circuits that are serviced from one pump supply.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Divisional Accuracy at Minimum Input Flow	±6.5%
Divisional Accuracy at Max Input Flow	±3.5%
Pressure Drop at Minimum Rated Input Flow	2 bar
Pressure Drop at Maximum Rated Input Flow	18 bar
Rated Input Flow with 50/50 Split	12 - 60 L/min.
Rated Input Flow with 40/60 Split	9,4 - 47 L/min.
Rated Input Flow with 33/67 Split	8,4 - 42 L/min.
Seal kit - Cartridge	Buna: 990032007
Seal kit - Cartridge	Polyurethane: 990032002
Seal kit - Cartridge	Viton: 990032006

CONFIGURATION OPTIONS

Model Code Example: FSDDXAN

CONTROL	(X) FLOW SPLIT	(A) SEAL MATERIAL	(N)
X Not Adjustable	A 50/50 B 40/60 C 33/67	N Buna-N V Viton	